



PRODUCTS RANGES of ATTACHMENTS

CRUSHER series

- Excellent crushing power
- HARDOX steel used for part of main body and Jaw , so that longer life time applied
- Operating efficiency has been upgraded by simple Jaw change for steel cutter and demolition
- Two pin, Hydraulic Motor Rotating type
- Specification



Description	Unit	TWO CYLINDER		
		TPMC 1600II	TPMC 3000II	TPMC 4000II
Operating Weight	kg	1680	2630	6100
Overall Length	mm	1945	2420	3395
Opening Width	mm	950	1100	1570
Middle Cutting Force	ton	110	175	283
Operating Oil pressure	kg/cm ²	300	320	350
Carrier Weight	ton	18~26	26~32	45~52

COMPACTOR

Description	Unit	CP 10	CP 30	CP 60	CP 80	CP 100
Tramping Power	kgf	1500	2500	6000	9000	11000
Max. Vibration	rpm	2400	2400	2400	2400	2400
Oil Flow Rate	ℓ/min	40	60	120	151	165
Operating Oil pressure	kg/cm ²	80~120	100~130	110~160	130~180	150~210
Operating Weight	kg	168	308	692	986	1171
Tramping Area	mm	558X502	850X460	990X760	1300X850	1484X950
Carrier Weight	ton	1~2	3~7	8~17	18~28	28~35



High effective in hardening of the simple road works

- High quality of pressure motor is applied to all of compactor
- All in one block oil flow control valve
- High effective in hardening at narrow ditch